

Serial No. 10/360,023

- 2 -

51412sh

CLAIM AMENDMENTS

1. (Currently Amended) A reconfigurable frequency selective surface (FSS) comprising:
a plurality of conducting patches supported on a first surface of a dielectric material; and
a plurality of switches, each switch electrically interconnecting at least two of the plurality of
conducting patches when the switch is selected,

wherein a first ensemble of switches is selectable so as to provide a first configuration of
electrically interconnected conducting patches, and

a second ensemble of switches is selectable so as to provide a second configuration of
electrically interconnected conducting patches,

the reconfigurable FSS being part of an artificial magnetic conductor (AMC) ground plane of an
antenna, the AMC further including the dielectric material and a conducting sheet on a second surface
of the dielectric material.

2. (Original) The reconfigurable FSS of claim 1, wherein the first configuration of electrically
interconnected conducting patches provides a first resonance frequency, and

the second configuration of electrically interconnected conducting patches provides a second
resonance frequency.

3. (Original) The reconfigurable FSS of claim 1, wherein the first configuration of electrically
interconnected conducting patches comprises a repeated unit cell pattern of electrically interconnected
conducting patches.

4. (Original) The reconfigurable FSS of claim 3, wherein the first configuration of electrically
interconnected conducting patches comprises a two-dimensional array of unit cell patterns of electrically
interconnected conducting patches.

5. (Original) The reconfigurable FSS of claim 1, wherein the plurality of conducting patches is
disposed in a square or rectangular grid pattern on the first surface of the dielectric material.

Serial No. 10/360,023

- 3 -

51412sh

6. (Original) The reconfigurable FSS of claim 1, wherein each conducting patch has a square or rectangular shape.

7. (Original) The reconfigurable FSS of claim 1, wherein the plurality of conducting patches is arranged in a plurality of fractal arrays.

8. (Currently Amended) The reconfigurable FSS of claim 1, ~~wherein a second surface of the dielectric material supports a conducting sheet, wherein the first configuration provides an artificial magnetic conductor having a first resonance frequency~~ wherein the FSS has a doubly periodic structure.

9. (Currently amended) A reconfigurable frequency selective surface (FSS) comprising a plurality of conducting patches, the conducting patches being supported on a ~~non-conducting~~ first surface of a dielectric material,

the conducting patches being selectively electrically interconnected in an electrical interconnection configuration,

wherein a resonance frequency of the frequency selective surface ~~can be adjusted~~ is adjustable through a modification of the electrical interconnection configuration,

the reconfigurable FSS being part of an artificial magnetic conductor (AMC), the AMC further including the dielectric material and a conducting sheet on a second surface of the dielectric material.

10. (Original) The reconfigurable FSS of claim 9, wherein the FSS provides a first resonance frequency corresponding to a first electrical interconnection configuration, and a second resonance frequency corresponding to a second electrical interconnection configuration,

wherein the first electrical interconnection configuration and the second electrical interconnection configuration are electrically selectable.

11. (Original) The reconfigurable FSS of claim 10, wherein the first resonance frequency is an integer multiple of the second resonance frequency.

Serial No. 10/360,023

- 4 -

51412sh

12. (Original) The reconfigurable FSS of claim 9, wherein the non-conducting surface is a first surface of a dielectric layer.

13. (Original) The reconfigurable FSS of claim 12, wherein a second surface of the dielectric layer supports an electrically conductive layer.

14. (Currently Amended) The reconfigurable FSS of claim [[13]] 2, wherein at least one resonance frequency of the frequency selective surface corresponds to behavior as an artificial magnetic conductor the FSS has a doubly periodic structure.

15. (Original) The reconfigurable FSS of claim 9, wherein the modification of the electrical interconnection configuration is achieved by providing electrical signals to an array of switches.

16. (Currently Amended) ~~An electromagnetic reflector including the reconfigurable FSS of claim 9~~ The FSS of claim 9, wherein the artificial magnetic conductor (AMC) is used as an electromagnetic reflector.

17. (Currently Amended) ~~An electromagnetic absorber including the reconfigurable FSS of claim 9~~ The FSS of claim 9, wherein the artificial magnetic conductor (AMC) is used as an electromagnetic reflector.

18. (Currently Amended) ~~An antenna system including the reconfigurable FSS of claim 9~~ The FSS of claim 9, wherein the artificial magnetic conductor (AMC) is used as a ground plane for an antenna.

19. (Original) An artificial magnetic conductor (AMC), the AMC comprising:
a dielectric material having a first surface and a second surface;
an electrically conducting layer substantially adjacent to the first surface of the dielectric

Serial No. 10/360,023

- 5 -

51412sh

material; and

a plurality of electrically conducting patches supported by the second surface of the dielectric material;

wherein the electrically conducting patches have an electrical interconnection configuration, the electrical interconnection configuration being reconfigurable so as to change a resonance frequency of the reconfigurable AMC.

20. (Original) The AMC of claim 19, wherein the electrical interconnection configuration is controlled by a plurality of electrical switches.

21. (Original) The AMC of claim 20, wherein the electrical switches comprise transistors.

22. (Original) The AMC of claim 20, wherein the electrical switches comprise resonant circuits.

23. (Original) The AMC of claim 19, wherein the interconnection configuration comprises a repeated pattern of unit cell interconnection configurations.

24. (Original) The AMC of claim 19, wherein the interconnection configuration is reconfigurable using electrical signals.

25. (Original) The AMC of claim 19, wherein the interconnection configuration for incident electromagnetic radiation is reconfigurable through a change in the frequency of the incident electromagnetic radiation.

[[27]] 26. (Original) An artificial magnetic conductor (AMC), the AMC comprising:

a dielectric material having a first surface and a second surface;

an electrically conducting layer substantially adjacent to the first surface of the dielectric material; and

a plurality of electrically conducting patterns supported by the second surface of the dielectric

